REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LJC 01/15/09'		

SINGLE ROW
N:NUMBER OF CONTACTS
A/B:CUSTOMER LENGTH AVAILABLE



TABLE A:

TYPE	Dimension	
	A	B
1	3.00	6.00
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		

NOTES:

1. ELECTRICAL CHARACTERISTICS:
   1.1 CONTACT RESISTANCE: 20mΩ Max.
   1.2 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
   1.3 INSULATION RESISTANCE: 1000MΩ Min.
2. ENVIRONMENT CHARACTERISTICS:
   2.1 TEMPERATURE RANGE: -40°C~+105°C.
3. PRODUCT NUMBER CODE:
   DS1021-01- X X X X
   - DIM A & B TYPE
     1: TYPE 1
     ⋮
   - CONTACT PLATING
     8: FULL GOLD FLASH
     6: TIN
   - MOUNTING TYPE
     V: V/T TYPE
   - No. OF CONTACTS
     2*2~2*40
     1*1~1*40

CONNFLY
Tel:86-574-63508787
Fax:86-574-63510812
E-mail:sale@zhenqin.com.cn
Http://www.connfly.com
Add:East Industry Zone, Lingyan Town, Yixi Ningbo China
P.C:315300

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1021-01-XXXXX		

PROJECTION		TITLE	PIN HEADER PITCH 2.54mm V/T TYPE H=4.3mm
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1021-01 SERIES

晨翔电子有限公司
CONNFLY ELECTRONIC CO. LTD